



The Epson All-in-One EcoTank L3550 and L5590 are designed to maximise your print productivity and convenience at the office. The upgraded PrecisionCore Printhead enables even faster printing speeds and replaceable maintenance box reduces repair downtime, improving efficiency. Both printers come with a full suite of connectivity features, including wireless connectivity and enabling direct printing from smart devices. Download Epson Smart Panel app to your mobile device and turn it into an intuitive control centre that enables you to power On/Off, set up, monitor your printer and ink level effortlessly. Experience this high-speed all-in-one printing solution today.













Epson

 \Box

Epson Smart Panel

Replaceable Maintenance



IT'S IN THE DETAILS.

Productivity Meets Durability

With PrecisionCore Printhead enabled, L3550 and L5590 has faster printing speed at 15/8 ipm. Improved mechanical design on parts that support paper feed-out contributes to longer product life - 2 years or 50,000 pages**.

Sustainability in Mind

Reduce power consumption through Heat-Free Technology. With hardware made from 30% recycled plastic¹, utilising 84% less consumables compared to ink cartridge models² and over 80% recycled cardboard packaging, carbon footprint is minimised.







Simplify User Interface

New concept of Flip UI simplifies user operation. Preset your frequently used functions as different cards, reducing the hassle of going through numerous setting parameters.

Available only on L5590. ** 2-year warranty or 50,000 pages, whichever comes first, printhead included.

Virgin plastic savings equivalent to approximately 250 plastic spoons, calculated as 3g of High Impact Polystyrene (HIPS) plastic spoon. Ratio of the amount of recycled plastic weight to overall plastic component weight of the hardware. The amount of recycled contents and recycled material varies depending on the model, manufacturing time and site.
 Material weight comparison of consumables (including packaging) between Epson ink cartridges of WF2630 series and Epson ink bottles of L5590/3550 series.

SPECIFICATIONS

Product Name	L3550	L5590	
Printer Type	Print, Scan and Copy	Print, Scan, Copy, Fax with ADF	
Printing			
Printing Technology	PrecisionCore Printhead		
lozzle Configuration	400 x 1 nozzles Black, 128 x 1 nozzles per Colour (Cyan, Magenta, Yellow)		
rint Direction	Bi-directional printing		
Maximum Resolution	4800 x 1200 dpi (with Variable-Sized Drople	t Technology)	
Minimum Ink Droplet Volume	3.3 pl		
rint Speed ^{*1} Draft Text - Memo, A4 (Black ^{#1} / Colour ^{#2})	Up to 33.0 ppm / 20.0 ppm		
ISO 24734, A4 (Black / Colour)	Simplex: Up to 15.0 ipm / 8.0 ipm		
First Page Out Time (Black / Colour)	Approx. 10 sec / 16 sec		
Photo Default - 10 x 15 cm / 4 x 6"2#3	Approx. 69 sec / 90 sec		
(Border / Borderless)	- pp		
rinter Language	ESC/P-R, ESC/P Raster		
utomatic 2-sided printing	No		
Copying			
Copy Speed	0: 1 11 1 10 0: (55:		
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 10.8 ipm / 5.5 ipm	L Approv. 60 and / 80 and	
ISO 29183, A4 (Black / Colour), ADF Copy Quality	Standard	Approx. 60 sec / 82 sec Standard / High	
Maximum Copies from Standalone	30 copies	99 copies	
Maximum Copy Resolution	600 x 600 dpi	_ aa cobies	
Maximum Copy Size	A4, LTR	Legal	
canning	/AT, E111	Legal	
canner Type	Flatbed color image scanner		
ensor Type	CIS		
ones. Type Optical Resolution	1200 x 2400 dpi		
faximum Scan Area	216 x 297 mm (8.5 x 11.7")	216 x 297 mm (8.5 x 11.7")	
canner Bit Depth	·		
Colour	48-bit input, 24-bit output		
Grayscale	16-bit input, 8-bit output		
Black & White	16-bit input, 1-bit output		
Scan Speed (Flatbed / ADF (Simplex)	44	110 000 / 5 0 1000	
Monochrome 200 dpi	11 sec	12 sec / 5.0 ipm	
Colour 200 dpi ax Function (L5590 only)	28 sec	29 sec / 5.0 ipm	
ype of FAX	Walk-up Black-and-White and Colour Fax Ca	holpility	
Receive Memory / Page Memory	1.1 MB, Page memory up to 100 pages	раошту	
Error Correction Mode	ITU-T T.30		
AX speed (data transfer rate)	Up to 33.6 kbps, Approx. 3 sec / page		
AX Resolution	Up to 200 x 200 dpi		
ransmission Paper Size	ор то 200 х 200 ар.		
Flatbed	Letter, A4		
ADF	A4, LTR, 8.5 x 13", Legal, Oficio 9, Mexico-Oficio, Indian-Legal		
Receiving Paper Size	Letter, A4, Legal		
Speed Dial / Group Dial	Up to 100 numbers, 99 groups		
Fax Features	PC Fax (Transmission / Receive), Automatic I		
NEE (15500 L.)	Only), Transmit Reservation, Polling Reception	n	
ADF Function (L5590 only) Support Paper Thickness	C4 OF com		
Paper Capacity	64 - 95 gsm 30 sheets		
Paper Handling	00 3116613		
Paper Feed Method	Friction feed		
Number of Paper Trays	1		
Paper Hold Capacity			
Input Capacity	Up to 100 sheets of Plain Paper (80 g/m²), 2	0 sheets of Premium Glossy Photo Paper	
Output Capacity		to 20 sheets of Premium Glossy Photo Pape	
Paper Size	A4, A5, A6, B5, B6, 100 x 148 mm, Indian-l	egal (215 x 345 mm), Letter,	
	8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 5 x	7", Envelopes #10, DL, C6	
Maximum Paper Size			
	215.9 x 1200 mm (8.5 x 47.24")		
Print Margin	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom set	ings in printer driver*3	
Print Margin nterface	0 mm top, left, right, bottom via custom set	ings in printer driver ^{*3}	
Print Margin nterface USB	0 mm top, left, right, bottom via custom sett USB 2.0		
rrint Margin nterface ISB letwork	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct		
rint Margin nterface ISB Isb Isb Isb Isb Isb Isb Isb Is	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di	
rrint Margin nterface ISB letwork letwork Protocol letwork Management Protocols	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di	
rrint Margin rterface ISB letwork letwork Protocol letwork Management Protocols Mobile/Software and Cloud Printing Epson Connect	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Prin	_ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver	
rint Margin Iterface ISSB Iletwork Iletwork Protocol Iletwork Management Protocols Iobile/Software and Cloud Printing Epson Connect Other Mobile Solutions	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS,	_ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver	
rint Margin nterface SB letwork letwork Protocol letwork Management Protocols flobile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson i	_ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD at Driver Smart Panel	
Print Margin Interface USB Jetwork Jetwork Protocol Jetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Prin	_ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD nt Driver	
Print Margin Interface JSB JSB Jetwork Network Protocol Jetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson S	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel	
Print Margin Interface JSB JSB Jetwork Network Protocol Jetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi DimDNS, SLP, WSD, LLTD Int Driver Smart Panel 1.44" Colour LCD Panel	
Print Margin Interface JSB JSB Jetwork Network Protocol Jetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
Print Margin Interface USB Jetwork Jetwork Protocol Jetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel Control Panel Printer Software	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
Print Margin Interface INSB Interface INSB Interface INSB Interface INSB Interface Int	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson S N/A Windows XP SP3 / XP Professional x64 SP/ Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
Print Margin Interface INSB Interface INSB Interface INSB Interface INSB Interface Int	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson S N/A Windows XP SP3 / XP Professional x64 SP/ Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
rrint Margin riterface ISB letwork letwork Protocol letwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
rrint Margin riterface ISB letwork letwork Protocol letwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Irrinter Software Operating System Compatibility Clectrical Specifications lated Voltage lated Frequency Inter Sonumption	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
rint Margin riterface ISB letwork letwork Protocol letwork Management Protocols flobile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rrinter Software perating System Compatibility clectrical Specifications lated Voltage lated Frequency lower Consumption Operating	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
rrint Margin riterface ISB letwork letwork Protocol letwork Management Protocols Abbile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rinter Software pperating System Compatibility letetrical Specifications lated Voltage lated Frequency lower Consumption Operating Standby	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2./ Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 pported for Windows Server OS	
rrint Margin riterface ISB letwork letwork Protocol letwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rrinter Software operating System Compatibility clectrical Specifications lated Voltage lated Frequency lower Consumption Operating Standby Sleep	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sur Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022	
Print Margin Interface ISB Ietwork Ietwork Protocol Ietwork Management Protocols Aboile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel COD Screen Printer Software Operating System Compatibility Cilectrical Specifications Rated Voltage Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power Off	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel 2./ Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 pported for Windows Server OS	
rrint Margin tterface ISB letwork letwork Protocol letwork Management Protocols flobile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rrinter Software pperating System Compatibility clectrical Specifications lated Voltage lated Frequency tower Consumption Operating Standby Sleep Power Off loise Level	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson S N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 pported for Windows Server OS	
Arint Margin Interface ISB Idetwork Idetwork Protocol Idetwork Management Protocols Interface Idetwork Management Protocols Idetwork Man	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are suff Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A),	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi D mDNS, SLP, WSD, LLTD nt Driver Smart Panel 1.44" Colour LCD Panel 2/ Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 pported for Windows Server OS 0.9 W	
Print Margin Interface ISB Idetwork Idetwork Protocol Idetwork Management Protocols Anobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel Con Screen Printer Software Operating System Compatibility Clectrical Specifications Rated Voltage Rated Frequency Prower Consumption Operating Standby Sleep Power Off Iolise Level OC Printing / Premium Glossy Photo Paper Rest Photo	0 mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 41 / 41 dB(A)	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD Int Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 apported for Windows Server OS 0.9 W	
Print Margin Interface ISB Idetwork Idetwork Protocol Idetwork Management Protocols Anobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel Con Screen Printer Software Operating System Compatibility Clectrical Specifications Rated Voltage Rated Frequency Prower Consumption Operating Standby Sleep Power Off Iolise Level OC Printing / Premium Glossy Photo Paper Rest Photo	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson S N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 41 / 41 dB(A), Sound Power (Black / Colour) 6.8 / 6.0 B(A),	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD Int Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 poorted for Windows Server OS 0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 38 / 39 dB(Sound Power (Black / Colour) 6.7 / 6.0 B(A),	
rint Margin riterface ISB letwork letwork Protocol letwork Management Protocols Abbile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rinter Software pperating System Compatibility letetrical Specifications lated Voltage lated Frequency ower Consumption Operating Standby Sleep Power Off Loise Level IC Printing / Premium Glossy Photo Paper lest Photo IC Printing / Plain Paper Default*	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 4.1 / 4.1 dB(A), Sound Pressure (Black / Colour) 5.8 / 6.0 B(A), Sound Pressure (Black / Colour) 5.7 / 47 dB(A), Sound Pressure (Black / Colour) 5.7 / 47 dB(A), Sound Pressure (Black / Colour) 5.7 / 47 dB(A),	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel 2./ Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 / 2019 /	
Print Margin Interface USB Jetwork Jetwork Protocol Jetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel Con	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Prince Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP/Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are surfunced by the service of	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 pported for Windows Server OS 0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), Sound Power (Black / Colour) 5.4 / 47 dB(Order Code	
Print Margin Interface ISB Idetwork Idetwork Protocol Idetwork Management Protocols Anobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CDD Screen Printer Software Operating System Compatibility Color Col	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson 3 N/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 4.1 / 4.1 dB(A), Sound Pressure (Black / Colour) 5.8 / 6.0 B(A), Sound Pressure (Black / Colour) 5.7 / 47 dB(A), Sound Pressure (Black / Colour) 5.7 / 47 dB(A), Sound Pressure (Black / Colour) 5.7 / 47 dB(A),	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel 2./ Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 / 2019	
rint Margin nterface ISB letwork letwork Protocol letwork Management Protocols Abbile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Voltage Rated Frequency Prower Consumption Operating Standby Sleep Power Off Roise Level CP Printing / Premium Glossy Photo Paper Dest Photo PC Printing / Plain Paper Default* Epson Consumable Black Syan	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Prince Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP/Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are surfunced by the service of	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD at Driver Smart Panel 1.44" Colour LCD Panel 2/ Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 pported for Windows Server OS 0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), Sound Power (Black / Colour) 6.7 / 6.0 B(A), Sound Pressure (Black / Colour) 5.4 / 47 dB(Order Code	
Print Margin Interface JSB Network Network Protocol Network Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Bated Frequency Power Consumption Operating Standby Sleep	O mm top, left, right, bottom via custom sett USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DDNS, Epson iPrint, Epson Email Print, Remote Print Apple AirPrint, Mopria Print Service, Epson SN/A Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are sup Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 6.8 / 6.0 B(A), Sound Pressure (Black / Colour) 55 / 47 dB(A) Page Yield 4 4,300 pages	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Di mDNS, SLP, WSD, LLTD Int Driver Smart Panel 1.44" Colour LCD Panel 2 / Vista / 7 / 8 / 8.1 / 10 / 11 / 2019 / 2022 prorted for Windows Server OS 0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 38 / 39 dB(Sound Power (Black / Colour) 5.7 / 6.0 B(A), Sound Pressure (Black / Colour) 54 / 47 dB(Order Code 003	

Dimensions & Weight

L3550 Weight: 4.1 kg





*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



- *2 When printed on Epson Premium Glossy Photo Paper.
- $^{*}3$ Otherwise 3 mm top, left, right, bottom.
- $^{\star}4\,$ Default mode in accordance with ISO7779 for MFPs.
- *5 In accordance with ISO 24711/24712. Actual yields will vary considerably for reasons including images printed, print settings, temperature and hurnidity. Yields may be lower when printing infrequently or predominantly with one link colour. A variable amount of link remains in the cartridges after the "replace cartridge" signal. Part of the link from the first cartridges is used for priming the printer. Ink is used for both printing and print head maintenance. All links are used for both black and colour printing.

© 2022 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct at time of printing Printed December 2022